WALL MOUNT ANTENNA
380 - 520 MHz

BDA-PIA-450512-4-1

Product Features

- UHF Full Range
- Wall Mount Panel Antenna
- Max Power 50W
- For Indoor Use

Electric Specifications	Value
Frequency Range	380-520MHz
Polarization Type	Vertical
Gain	4dBi
3dB Beam-Width. H-Plan	150°
3dB Beam-Width. E-Plan	75°
VSWR	≤3.0
Input Impedance	50Ω
Max Input Power.	50W
Lightning Protection	DC Grounded

Mechanical Specifications	Value
Connector Type	N-Type Female
Cable	SFF-50-3
Cable length	30cm
Dimensions H*W*D (mm)	304*195*66（mm）
Radome Material	ABS
Radome color	white
Operating Temperature Rang	-40ºC/+60ºC
Rated Wind Velocity	60m/s

DOC HON-62090.00 • 11022020 • DMC
Fiplex is a registered trademark of Fiplex Communications, Inc .
Fiplex Communications, Inc. reserves the right to change specifications without prior notice.

Honeywell

WALL MOUNT ANTENNA
380 - 520 MHz

BDA-PIA-450512-4-1

VSWR:

Radiation Pattern:

DOC HON-62090.00 • 11022020 • DMC
Fiplex is a registered trademark of Fiplex Communications, Inc .
Fiplex Communications, Inc. reserves the right to change specifications without prior notice.

Honeywell Building Technologies
715 Peachtree Street NE
Atlanta, GA 30308
www.honeywell.com

HON-62090.00 • 11022020
©2020 by Honeywell International Inc. All rights reserved.
Unauthorized use of this document is strictly prohibited.
This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.
Country of origin: U.S.A.

THE FUTURE IS WHAT WE MAKE IT

Honeywell