OMNIDIRECTIONAL ANTENNA
763 - 869 MHz

BDA-FA-763869-2-1

Product Features

- Wide bandwidth,low VSWR,stable performance, Omnidirectional
- Small size, attractive appearance
- Regular ceiling installation, use conveniently

Electric Specifications	Value
Frequency Range	763-869MHZ
Polarization Type	Vertical
Gain	4dBi
3dB Beam-Width. H-Plan	360°
3dB Beam-Width. E-Plan	60°
VSWR	≤1.5
Input Impedance	50Ω
Max Input Power	50W
Lightning Protection	DC Grounded

Mechanical Specifications	Value
Connector Type	N-Type Female
Dimensions H*W*D (mm)	Φ65*190(mm)
Weight	1kg
Material	ABS
Color	Off-White
Operating Temperature Range	-40ºC/+60ºC
Rated Wind Velocity	60m/s

DOC HON-62104.00 • 11092020 • DMC

Honeywell

OMNIDIRECTIONAL ANTENNA
763 - 869 MHz

BDA-FA-763869-2-1

VSWR:

Radiation Pattern:

DOC HON-62104.00 • 11092020 • DMC

Honeywell Business Solutions
715 Peachtree Street NE
Atlanta, GA 30308
www.honeywell.com

HON-62104.00 • 11092020
©2020 by Honeywell International Inc. All rights reserved.
Unauthorized use of this document is strictly prohibited.
This document is not intended to be used for installation purposes. We try to keep our product information
up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.
Country of origin: U.S.A.

THE FUTURE IS WHAT WE MAKE IT

Honeywell