N MALE TO N FEMALE ADAPTER
0 - 6GHz

BDA-NMRA-NFRA

Product Features

- N female to N male adapter
- Right Angle 90º

Electrical Specifications	Value	
Impedance	50Ω	
Frequency range	0～6GHz	
Withstand Voltage	500V rms	
VSWR	Rigth Angle	≤ 1.25
Contact resistance	center contact	≤ 1mΩ
	outer contact	≤ 1mΩ
Insulation resistance	≥5000MΩ	

Mechanical Specifications	Value
Temperature range	-65°C～+165°C
Durability(matings)	＞500

Material Specifications	Value
Body	Brass Nickel Plated
Center conductor	Brass Gold plated
Crimping suite	Copper alloy Nickel plated
O-ring sealing	6146 silastic
Insulator	PTFE

DOC HON-62081.00 • 11122020 • DMC

Honeywell Business Solutions
715 Peachtree Street NE
Atlanta, GA 30308
www.honeywell.com

HON-62081.00 • 11122020
©2020 by Honeywell International Inc. All rights reserved.
Unauthorized use of this document is strictly prohibited.
This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.
Country of origin: U.S.A.

THE FUTURE IS WHAT WE MAKE IT

Honeywell