FIBER GLASS OMNI ANTENNA
763 - 869 MHz

BDA-FA-763869-2-2

Product Features

- PS700 & PS800 full band
- Omni Directional Antenna
- Max Power 50W
- Fiberglass

Electric Specifications	Value
Frequency Range	763-869MHz
Polarization Type	Vertical
Gain	2.15dBi
3dB Beam-Width. H-Plan	360°
3dB Beam-Width. E-Plan	80°
VSWR	≤1.5
Input Impedance	50Ω
Max Input Power.	50W
Lightning Protection	DC Grounded

Mechanical Specifications	Value
Connector Type	N-Type Female
Dimensions H*W*D (mm)	Φ22*210 (mm)
Radome Material	Fiberglass
Radome color	white
Operating Temperature Rang	-40ºC/+60ºC
Support Pole Diameter	φ30-φ60(mm)
Rated Wind Velocity	60m/s

DOC HON-62105.00 • 11092020 • DMC

Honeywell

FIBER GLASS OMNI ANTENNA
763 - 869 MHz

BDA-FA-763869-2-2

VSWR:

Radiation Pattern:

DOC HON-62105.00 • 11092020 • DMC

Honeywell Business Solutions
715 Peachtree Street NE
Atlanta, GA 30308
www.honeywell.com

HON-62105.00 • 11092020
©2020 by Honeywell International Inc. All rights reserved.
Unauthorized use of this document is strictly prohibited.
This document is not intended to be used for installation purposes. We try to keep our product information
up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.
Country of origin: U.S.A.

THE FUTURE IS WHAT WE MAKE IT

Honeywell