

# ENTERPRISE DAS MASTER

## 758 - 869 MHz

**HONBDA-x-EM4**

### Product Features

- Specifically designed for 700 MHz and 800 MHz, LMR and Public Safety Applications
- No need of "Front End BDA" or "POI", reduced infrastructure cost
- Channelized
- Programmable uplink squelch (per channel and time slot) for reduced UL noise contribution
- Software programmable channel selective or band selective operation, suitable for highly congested RF environments
- Centralized operation, single point of access
- AGC per channel and time slot
- Supports Over The Air (OTA) operation
- NFPA Compliant
- Preserves BTS Rx sensitivity
- Signal Booster functionality, TO MOBILE RF Port available
- Country of Origin: USA
- 3-year warranty
- IFC & NFPA compliance; UL2524 2nd Edition Listing



### Applications

- For P25 Ph1, P25 Ph2, DMR, TETRA, TETRAPOL, C2000, LTE (up to 960MHz) NXDN and Conventional Systems
- Indoor: tunnels, buildings, subways, airports, among others
- Outdoor: stadiums, canyons, dense urban areas, remote rural towns

Specifications	Value
Fiber Optic	Single mode
WDM	Yes
Optical wavelengths	1310 / 1550 nM
Operational bands	PS700, FirstNet, PS800
Number of channel filters	32 UL - 32 DL + 2 Bandwidth adjustable per band
Available channel filter BW	150 KHz, 100 KHz, 75 KHz, , 62.5 KHz, 50 KHz, 37.5 KHz, 25 KHz & 12.5 KHz
Group delay	Channel Selective 150KHz, 11.5µS Channel Selective 100KHz, 13.5µS Channel Selective 75KHz, 16.0µS Channel Selective 62.5KHz, 18.0µS Channel Selective 50KHz, 21.0µS Channel Selective 37.5KHz, 25.5µS Channel Selective 25KHz, 35.0µS Channel Selective 12.5KHz, 61.5µS or Band selective: 3.5 to 6.5µS, depending on BWA
Supported Fiber Loss	5dBo max
Optical return loss	>45dB
RF Input/Output Impedance	50Ω
Max Operational DL Input Power	-35dBm
DL manual attenuator	20dB in 1dB steps
Maximum UL output power	+24 dBm
UL IM and spurious generation	< -13dBm
UL manual attenuator	20dB in 1dB steps

# ENTERPRISE DAS MASTER 758 - 869 MHz

## HONBDA-x-EM4

Overall Gain (Master + Remote)	80dB
RF connectors	N(f)
Optical connectors	FC / APC
Number of Optical Ports	4
Noise figure	<9dB
AC Supply	110/220 VAC 50/60Hz
Power consumption	80W
DC Supply	Optional, 24 - 48 VDC
Housing	IP67 / NEMA4X
Environmental	EN 300 019 4.1
Temperature range	-22° to +131° F • -30° to +55° C
Humidity	<95% non condensing
Dimension and weight	See table
MTBF	>50,000 hours

Signal Booster Specifications	Value
RF Ports	To Base & To Mobile
Operational bands	PS700 + FirstNet, PS800
Number of band pass (TO MOBILE Port)	One per band
Bandwidth (TO MOBILE Port)	Full band
Composite Output Power, DL (TO MOBILE Port)	PS700 + FirstNet: 33dBm PS800: 33dBm
Overall Gain	80 dB

Control and Alarms	Value
Alarms report	Via Master Unit Local: USB (POWER STATUS, MU STATUS, RM STATUS)
Master Unit Configuration	Local: USB

Normative	Value
Standards	ITU T G 652 EN60825-1
FCC	FCC, CFR 47, Part 15, Subpart B, Class A digital devices
ETSI	EN301489-1; EN301489-18 EN60950-1; TS 101 789-1

Model	Type	PWR Supply	Dimension	Weight
HONBDA-A-EM4	MASTER 700 + FirstNet + 800 - CLASS A	AC	17.7 x 17.3 x 5.1 in	24 kg
HONBDA-D-EM4	MASTER 700 + FirstNet + 800 - CLASS A	DC	17.7 x 17.3 x 5.1 in	24 kg

DOC HON-62110.05 • 12152020 • DMC

**Honeywell Business Solutions**  
715 Peachtree Street NE  
Atlanta, GA 30308  
www.honeywell.com

HON-62110.05 • 12152020  
©2020 by Honeywell International Inc. All rights reserved.  
Unauthorized use of this document is strictly prohibited.  
This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.  
Country of origin: U.S.A.

**THE  
FUTURE  
IS  
WHAT  
WE  
MAKE IT**

**Honeywell**